Please type a plus sign (+) inside this box → +

PTO/SB/05 (4/98)
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No.	RCA 89,041
First Inventor or Application Identifier	Schneidewend et al.
Title	A System For Processing Programs And...
Express Mail Label No.	EL213822368US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. [X] * Fee Transmittal Form *(e.g., PTO/SB/17)*
(Submit an original and a duplicate for fee processing)

2. [X] Specification [Total Pages 28]
(preferred arrangement set forth below)
- Descriptive title of the Invention
- Cross References to Related Applications
- Statement Regarding Fed sponsored R & D
- Reference to Microfiche Appendix
- Background of the Invention
- Brief Summary of the Invention
- Brief Description of the Drawings *(if filed)*
- Detailed Description
- Claim(s)
- Abstract of the Disclosure

3. [X] Drawing(s) *(35 U.S.C. 113)* [Total Sheets 5]

4. Oath or Declaration [Total Pages 1]
a. [X] Newly executed (original or copy)
b. [ ] Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
i. [ ] DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

5. [ ] Microfiche Computer Program *(Appendix)*

6. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
a. [ ] Computer Readable Copy
b. [ ] Paper Copy (identical to computer copy)
c. [ ] Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. [X] Assignment Papers (cover sheet & document(s))
8. [ ] 37 C.F.R.§3.73(b) Statement *(when there is an assignee)* [ ] Power of Attorney
9. [ ] English Translation Document *(if applicable)*
10. [X] Information Disclosure Statement (IDS)/PTO-1449 [X] Copies of IDS Citations
11. [ ] Preliminary Amendment
12. [X] Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. [ ] * Small Entity Statement(s) *(PTO/SB/09-12)* [ ] Statement filed in prior application, Status still proper and desired
14. [ ] Certified Copy of Priority Document(s)
(if foreign priority is claimed)
15. [ ] Other: .....

16. **If a CONTINUING APPLICATION,** *check appropriate box, and supply the requisite information below and in a preliminary amendment:*
[ ] Continuation [ ] Divisional [ ] Continuation-in-part (CIP) of prior application No: _____/_____
Prior application information: *Examiner* _____ *Group / Art Unit:* _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

[ ] *Customer Number or Bar Code Label* *(Insert Customer No. or Attach bar code label here)* or [ ] *Correspondence address below*

Name	Joseph S. Tripoli GE & RCA Licensing Management Operation, Inc.				
Address	Two Independence Way, P.O. Box 5312 Patent Operations				
City	Princeton	State	NJ	Zip Code	08543-5312
Country	USA	Telephone	(609) 734-9400	Fax	(609) 734-9700

Name (Print/Type)	Alexander J. Burke	Registration No. (Attorney/Agent)	40,425
Signature	Alexander Burke	Date	12 November 1998

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Express Mail Label No. EL213822368US

PTO/SB/17 (2/98)
Approved for use through 9/30/2000 OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTAL

Patent fees are subject to annual revision on October 1. These are the fees effective October 1, 1997. Small Entity payments must be supported by a small entity statement, otherwise large entity fees must be paid. See Forms PTO/SB/09-12. See 37 C.F.R. §§ 1.27 and 1.28.

TOTAL AMOUNT OF PAYMENT ($) 1,082

Complete if Known	
Application Number	To Be Assigned
Filing Date	Herewith
First Named Inventor	Schneidewend et al.
Examiner Name	To Be Assigned
Group / Art Unit	Unknown
Attorney Docket No.	RCA 89,041

METHOD OF PAYMENT (check one)

1. [X] The Commissioner is hereby authorized to charge indicated fees and credit any over payments to:

Deposit Account Number: 07-0832
Deposit Account Name: GE & RCA Licensing Mgmt.

[X] Charge Any Additional Fee Required Under 37 C.F.R. §§ 1.16 and 1.17 [ ] Charge the Issue Fee Set in 37 C.F.R. § 1.18 at the Mailing of the Notice of Allowance

2. [ ] Payment Enclosed: [ ] Check [ ] Money Order [ ] Other

FEE CALCULATION

1. BASIC FILING FEE

Large Entity Fee Code	Large Entity Fee ($)	Small Entity Fee Code	Small Entity Fee ($)	Fee Description	Fee Paid
101	790	201	395	Utility filing fee	790
106	330	206	165	Design filing fee	
107	540	207	270	Plant filing fee	
108	790	208	395	Reissue filing fee	
114	150	214	75	Provisional filing fee	

SUBTOTAL (1) ($) 790

2. EXTRA CLAIM FEES

		Extra Claims		Fee from below	Fee Paid
Total Claims	24	-20** = 4	X	22	= 88
Independent Claims	5	- 3** = 2	X		= 164
Multiple Dependent					=

**or number previously paid, if greater; For Reissues, see below

Large Entity Fee Code	Large Entity Fee ($)	Small Entity Fee Code	Small Entity Fee ($)	Fee Description
103	22	203	11	Claims in excess of 20
102	82	202	41	Independent claims in excess of 3
104	270	204	135	Multiple dependent claim, if not paid
109	82	209	41	** Reissue independent claims over original patent
110	22	210	11	** Reissue claims in excess of 20 and over original patent

SUBTOTAL (2) ($) 252

FEE CALCULATION (continued)

3. ADDITIONAL FEES

Large Entity Fee Code	Large Entity Fee ($)	Small Entity Fee Code	Small Entity Fee ($)	Fee Description	Fee Paid
105	130	205	65	Surcharge - late filing fee or oath	
127	50	227	25	Surcharge - late provisional filing fee or cover sheet.	
139	130	139	130	Non-English specification	
147	2,520	147	2,520	For filing a request for reexamination	
112	920*	112	920*	Requesting publication of SIR prior to Examiner action	
113	1,840*	113	1,840*	Requesting publication of SIR after Examiner action	
115	110	215	55	Extension for reply within first month	
116	400	216	200	Extension for reply within second month	
117	950	217	475	Extension for reply within third month	
118	1,510	218	755	Extension for reply within fourth month	
128	2,060	228	1,030	Extension for reply within fifth month	
119	310	219	155	Notice of Appeal	
120	310	220	155	Filing a brief in support of an appeal	
121	270	221	135	Request for oral hearing	
138	1,510	138	1,510	Petition to institute a public use proceeding	
140	110	240	55	Petition to revive - unavoidable	
141	1,320	241	660	Petition to revive - unintentional	
142	1,320	242	660	Utility issue fee (or reissue)	
143	450	243	225	Design issue fee	
144	670	244	335	Plant issue fee	
122	130	122	130	Petitions to the Commissioner	
123	50	123	50	Petitions related to provisional applications	
126	240	126	240	Submission of Information Disclosure Stmt	
581	40	581	40	Recording each patent assignment per property (times number of properties)	40
146	790	246	395	Filing a submission after final rejection (37 CFR 1.129(a))	
149	790	249	395	For each additional invention to be examined (37 CFR 1.129(b))	

Other fee (specify) _____

Other fee (specify) _____

* Reduced by Basic Filing Fee Paid

SUBTOTAL (3) ($) 40

SUBMITTED BY				Complete (if applicable)	
Typed or Printed Name	Alexander J. Burke			Reg. Number	40,425
Signature	Alexander Burke	Date	12 November 1998	Deposit Account User ID	07-0832

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

A System for Processing Programs and System Timing Information Derived from Multiple Broadcast Sources

This is a non-provisional application of provisional application serial No. 60/092,616 by D. R. Schneidewend et al, filed July 13, 1998.

Field of the Invention

This invention is related to the processing of programs and associated content rating and system timing information received from multiple broadcast sources for program play, recording and playback.

Background of the Invention

In digital video and audio broadcast applications, packetized program information transmitted to a video decoder, such as a High Definition Television (HDTV) receiver, contains broadcast channels, e.g. Fox 5™, Channel 13™, from multiple broadcasters. The packetized program information of an individual broadcaster may contain the data content of several program sub-channels occupying the frequency spectrum previously occupied by a single analog broadcast channel. The sub-channels may comprise, for example, digital services including a main program channel, a financial service channel offering stock quotes, a sports news service channel and a shopping and interactive channel, all being conveyed within the 6 MHz bandwidth previously allocated to a single analog NTSC compatible broadcast channel.

The packetized program information of an individual broadcaster also contains ancillary information as well as the data content of the program sub-channels. The ancillary information includes system information and program specific data used in identifying and assembling packets comprising selected programs and also includes program guide and text information associated with the transmitted program data. In particular, the ancillary

system information includes system timing information providing a time clock reference enabling determination of a time at which a specific program is to be broadcast. The ancillary program specific data may include program content rating information (such as PG-13 etc.) enabling parental control of viewing using a conditional access system such as a V-chip type system, for example. The ancillary system timing and content rating information is typically encoded along with program data to conform to the requirements of a known standard. One such standard detailing an information protocol incorporating system timing and content rating information for broadcast applications is entitled, *Program and System Information Protocol for Terrestrial Broadcast and Cable*, published by the Advanced Television Systems Committee (ATSC), 10 November 1997, hereinafter referred to as the PSIP standard.

A number of problems may arise in a digital video system in processing system timing and program specific information from multiple broadcast sources. Specifically, problems arise in the use of the system timing information for scheduling program processing functions and for displaying a current time to a user. Problems also arise in providing a conditional access system that uses accurate program content rating information in authorizing access to programs whilst also providing desirable features such as the ability for a user to optionally override a previously set content rating limit. Thus there is a need to solve these problems and derivative problems.

Summary of the Invention

A system for initiating scheduled program processing functions such as program display, recording or playback, derives a time clock based on a current time reference indication produced by a particular broadcast source. The derived time clock is used in initiating scheduled processing functions for programs derived from the particular broadcast source and time clocks derived from sources other than the particular broadcast source are disregarded. The system may display a second time clock different to the derived time clock.

Brief Description of the Drawings

In the drawing:

Figure 1 is a block diagram of digital video receiving apparatus for processing system timing and program content rating information from multiple broadcast sources, according to the principles of the invention.

Figure 2 shows a flowchart for a method for scheduling and executing program processing functions and displaying a time clock, according to the invention.

Figure 3 shows a program guide user interface for initiating scheduling of program processing functions, according to the invention.

Figure 4 shows a flowchart for a method for conditioning access to programs based on program content ratings received from multiple broadcast sources, according to the invention.

Figure 5 shows a method for generating program specific information incorporating system timing and program content rating information, according to the invention.

Detailed Description of the Drawings

Figure 1 is a block diagram of a digital video receiving system for demodulating and decoding broadcast signals from multiple broadcast sources, according to the principles of the invention. Although the disclosed system is described in the context of a system for receiving terrestrial broadcast video signals incorporating ancillary program specific and timing information in MPEG compatible format, it is exemplary only. The MPEG data format is widely adopted and detailed in the MPEG2 (Moving Pictures Expert Group) image encoding standard,

hereinafter referred to as the "MPEG standard", (ISO/IEC 13818-1, 10th June 1994, and ISO/IEC 13818-2, 20th January 1995). The program specific and timing information may be of a variety of types. For example, it may comply with Program Specific Information (PSI) requirements specified in section 2.4.4 of the MPEG systems standard or it may comply with the previously mentioned PSIP standard or other ATSC standards. Alternatively, it may be formed in accordance with proprietary or custom requirements of a particular system.

The principles of the invention may be applied to terrestrial, cable, satellite, Internet or computer network broadcast systems in which the coding type or modulation format may be varied. Such systems may include, for example, non-MPEG compatible systems, involving other types of encoded datastreams and other methods of conveying program specific information. Further, although the disclosed system is described as processing broadcast programs, this is exemplary only. The term 'program' is used to represent any form of packetized data such as audio data, telephone messages, computer programs, Internet data or other communications, for example.

In the video receiver system of Figure 1, a broadcast carrier modulated with signals carrying audio, video and associated data representing broadcast program content is received by antenna 10 and processed by unit 13. The resultant digital output signal is demodulated by demodulator 15. The demodulated output from unit 15 is trellis decoded, mapped into byte length data segments, deinterleaved and Reed-Solomon error corrected by decoder 17. The corrected output data from unit 17 is in the form of an MPEG compatible transport datastream containing program representative multiplexed audio, video and data components. The transport stream from unit 17 is demultiplexed into audio, video and data components by unit 22 which are further processed by the other elements of decoder system 100. In one mode, decoder 100 provides MPEG decoded data for display and audio reproduction on units 50 and 55 respectively. In another mode, the transport stream from unit 17 is processed by decoder 100 to provide an MPEG compatible

datastream for storage on storage medium 105 via storage device 90.

A user selects for viewing either a TV channel (user selected channel-SC) or an on-screen menu, such as a program guide, by using a remote control unit 70. Controller 60 uses the selection information provided from remote control unit 70 via interface 65 to appropriately configure the elements of Figure 1 to receive a desired program channel for viewing. Controller 60 comprises processor 62 and processor 64. Unit 62 processes (i.e. parses, collates and assembles) system timing information and program specific information including program content rating, and program guide information. Processor 64 performs the remaining control functions required in operating decoder 100. Although the functions of unit 60 may be implemented as separate elements 62 and 64 as depicted in Figure 1, they may alternatively be implemented within a single processor. For example, the functions of units 62 and 64 may be incorporated within the programmed instructions of a microprocessor.

Controller 60 configures processor 13, demodulator 15, decoder 17 and decoder system 100 to demodulate and decode the input signal format and coding type. Further, controller 60 configures units 13, 15, and 17 for other communication modes, such as for receiving cable television (CATV) signals and for bi-directional communication via coaxial line 14 or for bi-directional (e.g. Internet) communication, for example, via telephone line 11. In an analog video mode, an NTSC compatible signal is received by units 13, 15 and 17 and processed by decoder 100 for video display and audio reproduction on units 50 and 55 respectively. Units 13, 15, 17 and sub-units within decoder 100 are individually configured for the input signal type by controller 60 setting control register values within these elements using a bi-directional data and control signal bus C.

The transport stream provided to decoder 100 comprises data packets containing program channel data and ancillary system timing information and program specific information including program content rating, and program guide information. Unit 22 directs the ancillary information packets to

controller 60 which parses, collates and assembles this information into hierarchically arranged tables. Individual data packets comprising the User selected program channel SC are identified and assembled using the assembled program specific information. The system timing information contains a time reference indicator and associated correction data (e.g. a daylight savings time indicator and offset information adjusting for time drift, leap years etc.). This timing information is sufficient for a decoder to convert the time reference indicator to a time clock (e.g. United States east coast time and date) for establishing a time of day and date of the future transmission of a program by the broadcaster of the program. This time clock is useable for initiating scheduled program processing functions including program play, program recording and program playback, for example. Further, the program specific information contains conditional access, network information and identification and linking data enabling the system of Figure 1 to tune to a desired channel and assemble data packets to form complete programs. The program specific information also contains ancillary program content rating information (e.g. an age based suitability rating), program guide information (e.g. an Electronic Program Guide - EPG) and descriptive text related to the broadcast programs as well as data supporting the identification and assembly of this ancillary information.

The program specific and system timing information is assembled by controller 60 into multiple hierarchically arranged and inter-linked tables. An exemplary PSIP compatible hierarchical table arrangement includes a System Time Table (STT), a Master Guide Table (MGT), a Channel Information Table (CIT), Event Information Tables (EITs) and optional tables such as Extended Text Tables (ETTs) and a Rating Region Table (RRT). The STT contains a time reference indicator and associated correction data sufficient for a decoder to establish a time of transmission of a program by a broadcast source accurate to within plus or minus 4 seconds, for example. The MGT contains information for acquiring program specific information conveyed in other tables such as identifiers for identifying data packets associated with the

other tables. The CIT contains information for tuning and navigation to receive a User selected program channel. The EIT contains descriptive lists of programs (events) receivable on the channels listed in the CIT. The ETT contains text messages describing programs and program channels.

The RRT contains program content rating information such as the MPAA (Motion Picture Association of America) or V-chip compatible rating information that is collated by region (e.g. by country or by state within the U.S.A.). Additional program specific information describing and supplementing items within the hierarchical tables is conveyed within descriptor information elements. Information associating a program content rating with a particular program from a particular broadcast source may be conveyed within a content advisory descriptor contained in an EIT or PMT. In other embodiments the system timing and program content rating information associating a specific program with a specific rating may be contained in other tables, data formats, or descriptors such as the caption service descriptor or the information may be conveyed in user definable data. Additional program content ratings are conveyed in vertical blanking intervals in NTSC compatible signals processed by analog processor 27 within decoder 100 in analog video mode. The program specific and system timing information acquired by controller 60 via unit 22 is stored within internal memory of unit 60. Controller 60 uses the acquired content rating and system timing information in conditioning access to programs and in scheduling program processing functions including program viewing, recording and playback.

Controller 60 employs the process of Figure 2 to execute scheduled program processing functions including program viewing, recording, and playback. In other embodiments, a process corresponding to the process of Figure 2 (and Figure 4) may be used to execute other scheduled functions including program transmission, program standards conversion, program encryption, decryption, scrambling, decoding and their derivative functions including the termination of any of these processing functions. In executing scheduled processing of a particular

program, controller 60 adaptively generates a scheduling time clock from a time reference indication (e.g. in the STT) provided by the broadcast source of the particular program. This generated scheduling clock is used to time the initiation of scheduled program processing functions. Previously derived time clocks (e.g. from other broadcast sources) are disregarded in initiating scheduled processing of this particular program. The scheduling time clock is re-synchronized to the STT time reference information provided by a particular broadcast source prior to initiating scheduled processing of any programs produced by that particular source.

These features address the problem of preventing application of incorrect program specific information parameters (parameters within the MGT, CIT, EIT, ETT and RRT etc.) across program boundaries. This may occur if program processing is scheduled using an inaccurate time clock such as a clock derived from a broadcast source other than the source of the specific program to be processed. A time clock inaccuracy of 10 seconds or more is quite possible under these conditions due to program broadcasting delays and other delays occurring in a system using multiple broadcast sources.

As a result of this time clock inaccuracy, the wrong program may be recorded (or viewed or played back) in overlap periods between initiation or termination of program recording and the actual broadcast time of the program. Further, a program may be erroneously recorded using the program specific information parameters of a previously processed program during program segments occurring in the overlap periods. Consequently, upon playback of the program, incorrect program specific parameters are applied during the overlap segments. This may cause faulty decoding including incorrect packet identification and acquisition or the use of incorrect program content ratings, for example. As a result, invalid and objectionable images may be transiently displayed to a user. Under such conditions a portion of an adult content rated program may be erroneously displayed to a child, for example.

Controller 60 employs the process of Figure 2 to schedule and execute program processing functions upon user initiation of a scheduling function. Following the start at step 200, controller 60 in step 203 schedules program viewing (including tuning and acquisition), recording or playback in response to a user scheduling command via the program guide interface of Figure 3 displayed on display 50 (Figure 1). Other embodiments may employ alternative user interfaces for this scheduling function.

In scheduling program viewing or recording via the program guide of Figure 3, a user navigates to the desired channel and program using menu icons 853 and 855. The user selects a program e.g. news program 849 by highlighting the news icon 849 and schedules the news program 849 for viewing or recording by selecting icon 805 or icon 810 respectively. A user may similarly schedule playback of a movie such as movie item 847 (Terminator II) from storage device 90 and medium 105 (Figure 1). The user schedules playback of the movie by highlighting the movie item 847 and selecting icon 815. In other embodiments a user may schedule program viewing, recording or playback by other methods such as by using remote unit 70 buttons rather than program guide icons 805, 810 and 815.

Upon user selection of icons 805 or 810 controller 60 stores the scheduled times of broadcast and termination of news item 849 in internal memory. Controller 60 determines scheduled times of broadcast and termination of news item 849 from stored program guide information previously derived from the EIT. Upon user selection of icon 815 controller 60 in conjunction with unit 37 (Figure 1) generates a scheduling menu enabling a user to enter a time for future playback of movie 847 or to select immediate playback of the movie. A user selects the control and navigation icons and enters times etc. using remote control 70 which supports cursor manipulation (or an alternative cursor based arrangement such as a mouse or keyboard system).

Returning to the process of Figure 2, controller 60 in step 205 configures units 13, 15 and 17 (Figure 1) and decoder 100 elements to receive packetized program information

containing a user selected program. Controller 60 configures processor 13, demodulator 15 and decoder 17 to receive the specific channel frequency and data format of the transmission channel of the broadcaster of the desired program (previously selected in step 203). In step 210 controller 60 acquires the packets comprising STT data from the broadcast source of the desired program by configuring demultiplexer 22 with the predetermined STT PIDs and table identification data (Table_ID). Thereby controller 60 acquires the STT data containing a current time reference indication and time correction data produced by the broadcast source of the desired program. The STT data is transmitted and acquired at predetermined periodic intervals (recommended by the PSIP standard to be at least once per second).

In step 215, in program recording and viewing modes, controller 60 derives a time clock using the acquired STT time reference indication (a value indicating the number of seconds elapsed since a base time, specifically since 12 a.m. January 6, 1980) together with STT correction data including an offset value and daylight savings time indicator (per PSIP standard section 6.1). The derived time clock consists of both a date and time and comprises year, month, day and time of day. In deriving the time clock from the time reference indication the following four values are computed:

1) Number of minutes from Base = (received seconds from Base)/60

2) Number of hours from Base = (received minutes from Base)/60

3) Number of days from Base = (hours from Base)/24

4) Number of years from Base = (days from Base)/(days per year), where,

days per year = 365, or 366 in a leap year

Note,

The Base in the above expressions is 12 a.m. January 6, 1980.

From the above four values the derived time clock components, year, month, day and time of day are determined as follows.

1) current year = Base year + number of years from Base,

2) current day of year = number of days from Base - (number of years from Base * days per year),

Also, the current month and day of the month are determined directly from the current year and the current day of year.

3) current hour of day = number of hours from Base - (number of days from Base * 24),

4) current minute of hour = number of received minutes from Base - (number of hours from Base * 60)

5) current second within the minute = number of received seconds from Base - (number of minutes from Base * 60)

Then the derived time clock is the current total time = current year, month, day, hour, minute and second. In addition, the derived time clock is corrected using STT correction data including an offset value and daylight savings time indicator per PSIP standard section 6.1 and Annex A (or by corresponding correction factors in non-PSIP compatible systems).

In step 215 in program playback mode, controller 60 uses an internal system clock synchronized with operation of storage device 90 for initiation of movie playback. In other embodiments, controller 60 may derive a scheduling clock from a variety of other forms of time clock data. It is advantageous that the time clock data used to derive the scheduling clock is synchronized with the time clock transmitted by the broadcast source in broadcasting the desired program. This is achieved, for

example, by using STT data from the broadcast source of the desired program in viewing and recording modes and by using a system clock synchronized with a playback device in playback mode. STT data and time clocks derived from STT data from broadcast sources other than the source of the desired program are disregarded in initiating scheduled processing of the desired program.

In step 220, controller 60 updates (i.e. corrects and re-synchronizes) an internally maintained and stored scheduling time clock with the time clock information derived in step 215. The scheduling clock is periodically updated in this manner from derived time clock values obtained from the updated STT data received at intervals of one second or less. In the time intervals between updating the scheduling clock from the STT data the scheduling clock is maintained using an internal crystal derived clock frequency within controller 60. Controller 60 in other embodiments may create and maintain separate scheduling clocks and/or STT derived time reference and correction information associated with each program broadcast source (e.g. one clock for each broadcast source) using the method of steps 205-215. In step 220, if no time clock reference information is available from the broadcast source of the desired program, controller 60 uses a previously derived scheduling clock. Controller 60 in step 225 initiates processing of the desired program at the scheduled processing time previously established in step 203. Controller 60 determines whether the times for initiating processing (previously scheduled in step 203) have arrived based on the scheduled clock determined in step 220.

Controller 60 in step 225 initiates processing of the desired program for viewing, recording or playback at the scheduled processing time by identifying and acquiring the packets comprising the desired program. Specifically, controller 60 and processor 22 (Figure 1) determine from the CIT the PIDs of video, audio and sub-picture streams in the packetized decoded transport stream input to decoder 100 from unit 17. The video, audio and sub-picture streams constitute the desired program being transmitted on selected channel SC. Processor 22 provides

MPEG compatible video, audio and sub-picture streams for to video decoder 25, audio decoder 35 and sub-picture processor 30 respectively. The video and audio streams contain compressed video and audio data representing the selected channel SC program content. The sub-picture data contains the EIT, ETT and RRT information associated with the channel SC program content.

Decoder 25 decodes and decompresses the MPEG compatible packetized video data from unit 22 and provides decompressed program representative pixel data to NTSC encoder 45 via multiplexer 40. Similarly, audio processor 35 decodes the packetized audio data from unit 22 and provides decoded and amplified audio data, synchronized with the associated decompressed video data, to device 55 for audio reproduction. Processor 30 decodes and decompresses sub-picture data received from unit 22.

Processor 30 assembles, collates and interprets EIT, RRT, and ETT data from unit 22 to produce formatted program guide data for output to OSD 37. OSD 37 processes the EIT, RRT and ETT and other information to generate pixel mapped data representing subtitling, control and information menu displays including selectable menu options and other items for presentation on the display device 50. The control and information menus that are displayed enable a user to select a program to view and to schedule future program processing functions including a) tuning to receive a selected program for viewing, b) recording of a program onto storage medium 105, and c) playback of a program from medium 105.

The control and information displays, including text and graphics produced by OSD generator 37, are generated in the form of overlay pixel map data under direction of controller 60. The overlay pixel map data from unit 37 is combined and synchronized with the decompressed pixel representative data from MPEG decoder 25 in encoder 45 via multiplexer 40 under direction of controller 60. Combined pixel map data representing a video program on channel SC together with associated sub-picture data is encoded by NTSC encoder 45 and output to device 50 for display.

In step 230 (Figure 2), controller 60 generates a second time clock for presentation to a user such as the displayed time clock item 857 (also comprising a date) depicted in the program guide of Figure 3, for example. The second time clock is different to the scheduling clock and is generated to prevent time change discontinuities that occur in the scheduling clock from being displayed and from disturbing a user. Controller 60 generates the second time clock a) by filtering the scheduling time clock values to prevent abrupt discontinuities e.g. by using a low pass filter, or b) by updating the second time clock in periods when it is not visible to a user. Alternatively, a second time clock may be used that is independent of the scheduling clock and is a) based on an internal clock of the controller 60 and decoder 100 system, b) is received on a channel that is separate and distinct from the program content channels, or c) is received embedded within a composite program guide that lists programs from multiple broadcast sources, for example. The process of Figure 2 terminates at step 235.

Controller 60 employs the method of Figure 4 to process packetized program information from different broadcast sources using functionally equivalent program specific information parameters including program content rating data dynamically selected from alternative broadcast sources. In processing packetized program information, controller 60 advantageously adaptively selects a program specific parameter based on the broadcast source of the parameter. The process of Figure 4 is also applicable to the scheduling of analog video NTSC compatible programs and to the acquisition and processing of rating information derived from vertical blanking intervals.

In the exemplary embodiment of Figure 4, controller 60 conditions access to programs based on program content ratings received from multiple broadcast sources that provide either analog or digital data. Controller 60 conditions access to programs in response to user commands entered via control and information menus generated by OSD unit 37 and displayed on unit 50 (as described in connection with Figure 2). The control and information menus enable a user to enter content rating profiles

for himself and others, upon providing entitlement data comprising a userid and a predetermined password, for example. A content rating profile allows a user to set a maximum rating limit threshold for individual users of decoder 100 according to a user selected rating system. A user may select rating limit thresholds according to one of a number of different rating systems such as the V-chip, MPAA, or other systems. Thereby decoder 100 enables parental control over access to broadcast programs by children and others. In addition, the control and information menus enable a user to override a selected preset maximum rating limit upon entry of authorization data such as a userid and password.

In executing the process of Figure 4 and following the start at step 300, controller 60 in step 303 initiates scheduling of program viewing (including tuning and acquisition), recording or playback. Controller 60 initiates scheduling in response to a user scheduling command via the program guide interface of Figure 3 as previously discussed. Controller 60 in step 305 configures units 13, 15 and 17 (Figure 1) and decoder 100 elements to receive composite program guide information from a first broadcast source. The composite program guide information contains program description and other information supporting assembly and decoding of packet data constituting individual programs produced by multiple different broadcast sources. Controller 60 configures processor 13, demodulator 15 and decoder 17 to receive the specific channel frequency and data format of the transmission channel provided by the first broadcast source. Thereby in step 305 controller 60, in conjunction with unit 22, acquires composite program guide information containing program specific information including a program content rating for the desired program from the first broadcast source. Also, in step 305 controller 60 stores the program specific information in internal memory and in step 310 retrieves the content rating of the desired program from a content advisory descriptor contained in an EIT of the stored program specific information. Controller 60 determines the rating system of the retrieved content rating (i.e. whether the desired program is rated according to a V-chip or

MPAA compatible system, for example) from an acquired RRT of the stored program specific information.

In step 315, controller 60 compares the retrieved program content rating with a maximum rating threshold limit contained in a predetermined user specific rating profile. The rating threshold limit determines the maximum program content rating that the present user of the decoder 100 system is authorized to access. If the content rating of the desired program does not exceed the maximum content rating threshold, controller 60 schedules processing of the desired program in step 315. The retrieved program content rating and maximum content rating threshold limit are compatible with a content rating system contained within the previously stored RRT. An exemplary age based rating system is depicted in the program guide of Figure 3 (items 860-872) and comprises TV-M, TV-14, TV-PG, TV-G, TV-Y7, TV-Y ratings.

A number of problems may occur in using content ratings from a composite program guide (or another rating information source) in scheduling processing of programs in the manner disclosed in steps 303-315. Specifically, problems may arise because a) the content rating supplied in the composite guide provided by the first broadcast source may be inaccurate, and b) the verification of user authorization performed in step 315 may be rendered invalid for a variety of reasons. The verification may be rendered invalid, for example, because either the program guide limit threshold is subsequently overridden and altered by an authorized user or because of a subsequent re-rating of the content of the desired program.

Consequently, controller 60 in step 320 acquires a second content rating of the desired program from program specific information provided by the broadcast source of the desired program. The content rating from this second broadcast source is acquired reasonably close to the time of program broadcast to enable a current and reliable second validation of user authorization to access the desired program. In step 325, controller 60 converts the content rating acquired from the second source (the broadcaster of the desired program) to be compatible

with the content rating system used by the first source (the composite guide broadcaster). Controller 60 converts the content rating using predetermined equivalence mapping information for mapping content ratings of one broadcast source to a rating system of another source.

In step 330, if the ratings acquired from the first and second broadcast sources are different, controller 60 selects between them. Once selected, the content rating is used in further processing and may be used by controller 60 in step 330 to update an existing different rating such as a rating displayed in the program guide of Figure 3, for example. Controller 60, in step 330, selects a program specific information parameter from the broadcast source deemed to be the most reliable and accurate considering a) the type of parameter being selected (a content rating in this example), and b) the time and stage in the processing scheme at which the parameter is being processed. A program specific information parameter from one broadcast source may be deemed more reliable at a particular point in time than an equivalent parameter from another source. Consequently, parameter selection may be advantageously varied based on the source of the parameter and time and processing stage at which it is acquired. In other embodiments, the rating conversion step 325 may be unnecessary and it may alternatively be used to convert a rating to the system of the second source or to a third and different system. It is advantageous in conditioning access based on program content ratings to select the content rating that: a) is provided from the broadcast source of the desired program, and b) is the most recently acquired rating especially if the rating is acquired substantially close to the time of broadcast of the desired program.

In step 335, controller 60 uses the rating selected in step 330 to perform a second validation of user authorization to access the desired program in the manner described in connection with step 315. Specifically, controller 60 compares the retrieved program content rating with the maximum rating threshold limit contained in the predetermined user specific rating profile. Upon successful validation, controller 60 in step 337 initiates processing

of the desired program by configuring demultiplexer 22 with the PIDs for identifying and acquiring the packets comprising the datastreams constituting the desired program. Decoder 100 processes the identified packets of the desired program for viewing, recording or playback in the manner previously described in connection with Figure 2. The process of Figure 4 terminates at step 340.

The process of Figure 4 is also used in conditioning access to analog video programs and in the acquisition and processing of program content ratings derived from the vertical blanking intervals of NTSC compatible analog video signals. Consequently steps 303-320 similarly involve scheduling analog video processing and tuning to analog video sources for deriving content ratings (e.g. V-chip compatible ratings) from NTSC compatible vertical or horizontal blanking intervals. Further, the mapping, selection, validation and processing of steps 325-337 use ratings derived from analog video signal as well as from digital program specific information.

Figure 5 shows a method for generating program specific information incorporating system timing and program content rating information, according to the invention. The method may be employed at an encoder for broadcasting video data such as the data received by antenna 10 of Figure 1 or the method may be employed within a decoder unit such as within controller 60 of Figure 1 in a storage mode, for example.

In a storage mode of the system of Figure 1, the corrected output data from unit 17 is processed by decoder 100 to provide an MPEG compatible datastream for storage. In this mode, a program is selected for storage by a user via remote unit 70 and interface 65. Processor 22, in conjunction with controller 60 forms condensed system and program specific information including STT, MGT, CIT, EIT, ETT and RRT data containing the advantageous features previously described. The condensed information supports decoding of the program selected for storage but excludes unrelated information. Controller 60, in conjunction with processor 22 forms a composite MPEG compatible datastream containing packetized content data of the selected program and

associated condensed program specific information. The composite datastream is output to storage interface 95.

Storage interface 95 buffers the composite datastream to reduce gaps and bit rate variation in the data. The resultant buffered data is processed by storage device 90 to be suitable for storage on medium 105. Storage device 90 encodes the buffered datastream from interface 95 using known error encoding techniques such as channel coding, interleaving and Reed Solomon encoding to produce an encoded datastream suitable for storage. Unit 90 stores the resultant encoded datastream incorporating the condensed program specific information on medium 105.

An encoder employs the method of Figure 5 for generating system and program specific information including STT, MGT, CIT, EIT, ETT and RRT data and descriptors for each broadcaster and for combining the information in a composite datastream. The generated information may be transmitted to a decoder system such as the system of Figure 1 for reception by antenna 10 and subsequent decoding as previously described for example. Following the start at step 400 of Figure 5, STT, MGT, CIT, EIT, ETT and RRT data and descriptors for each broadcaster is generated in steps 405 and 410. Specifically, a CIT is generated in step 405. The CIT contains channel and program identification information enabling acquisition of available broadcast programs and channels produced by an individual broadcaster. The CIT incorporates channel identification numbers and packet identifiers for identifying individual packetized datastreams that constitute individual programs to be transmitted on particular channels. The generated CIT also incorporates items linked to listed program channels including a program number, a language code indicator, and a stream type identifier, as previously described in connection with Figure 1.

In step 410, an EIT is generated containing program guide information including descriptive lists of programs (events) receivable on the channels listed in the CIT. The EIT is generated to include a content advisory descriptor containing program content ratings selected and processed from rating information provided by multiple broadcast sources in the manner described

in connection with Figure 4. The EIT associates a specific program with a specific rating. An ETT and an RRT are also generated in step 410. The ETT contains text messages describing programs, for example, and the RRT contains program content rating information for various rating systems as previously described. In step 410, an MGT is also generated containing data identifiers enabling the identification and assembly of CIT, EIT, and RRT information. The MGT also conveys table size information for the previously generated CIT, EIT, ETT and RRT. An STT is also generated in step 410 containing a time reference indicator and associated correction data sufficient for a decoder to establish a time of transmission of a program by the program broadcaster.

In step 415, the STT, MGT, CIT, EIT, ETT and RRT data and descriptors generated for each broadcaster in steps 405 and 410 are formed into composite system and program specific information for multiple broadcast sources. The composite system and program specific information is advantageously formed to associate individual STT time references with their corresponding broadcast sources. In step 420, the composite information produced in step 415 is combined with video and audio program representative components for multiple channels and is formatted into a transport stream for output. In step 423, the output transport stream is further processed to be suitable for transmission to another device such as a receiver, video server, or storage device for recording on a storage medium, for example. The processes performed in step 423 include known encoding functions such as data compression Reed-Solomon encoding, interleaving, scrambling, trellis encoding, and carrier modulation. The process is complete and terminates at step 425. In the process of Figure 5, multiple CIT, EIT, ETT and RRT tables may be formed and incorporated in the program specific information in order to accommodate expanded numbers of channels.

The architecture of Figure 1 is not exclusive. Other architectures may be derived in accordance with the principles of the invention to accomplish the same objectives. Further, the functions of the elements of decoder 100 of Figure 1 and the process steps of Figures 2, 4 and 5 may be implemented in whole

or in part within the programmed instructions of a microprocessor. In addition, the principles of the invention apply to any form of MPEG or non-MPEG compatible electronic program guide. A datastream formed according to the invention principles may be used in a variety of applications including video server or PC type communication via telephone lines, for example. A program datastream with one or more components of video, audio and data formed to incorporate system and program specific information according to invention principles may be recorded on a storage medium and transmitted or re-broadcast to other servers, PCs or receivers.

What is claimed is:

1. A system for initiating scheduled program processing functions for use in a video decoder receiving packetized program information from different broadcast sources, said packetized program information from an individual broadcast source containing program content, system timing and program specific information data, comprising:

selection means for selecting a desired program produced by a broadcast source;

means for tuning to receive packetized program information containing said program; and

a processor for identifying and acquiring system timing data comprising a current time reference indication provided by said broadcast source in said packetized program information wherein

said processor derives a time clock based on a current time reference indication produced by a particular broadcast source and uses said derived time clock in initiating scheduled processing functions for programs derived from said particular broadcast source.

2. A system according to claim 1 wherein, in initiating scheduled processing functions

said processor disregards a time clock derived from a current time reference indication produced by a source other than said particular broadcast source.

3. A system according to claim 1, wherein

said processor updates a stored scheduling time clock with a clock value derived from a current time reference indication produced by said particular broadcast source prior to using said scheduling time clock in initiating scheduled processing functions for programs derived from said particular broadcast source.

4. A system according to claim 1, wherein in the absence of a valid current time indication being available from said particular broadcast source

said processor initiates scheduled processing functions using a clock value derived from a current time reference indication produced by a source other than said particular broadcast source.

5. A system according to claim 1, wherein

said processor derives a second time clock for display to a user and said second time clock is different to said derived time clock used in initiating scheduled processing functions for programs.

6. A system according to claim 5, wherein

said second time clock is a filtered time clock to prevent a user from seeing an abrupt time change discontinuity.

7. A system according to claim 5, wherein

said second time clock is updated during periods when said second time clock is not displayed to prevent a user from seeing an abrupt time change discontinuity.

8. A system according to claim 5, wherein

said second time clock is updated using current time reference indications independently of the broadcast source of said current time reference indications.

9. A system according to claim 5, wherein

said second time clock is updated using current time reference indications from a single source.

10. A system according to claim 1, wherein

said processor initiates a scheduled processing function in response to a user selection made via a displayed electronic program guide.

11. A system according to claim 1, wherein

said processor initiates scheduled processing functions including at least one of, a) program recording, b) program playback and c) program selection and display.

12. A system according to claim 1, wherein

said tuning means tunes to receive said packetized program information transmitted on a particular RF transmission channel carrier frequency used by said particular broadcast source, and

said processor identifies and acquires system timing data provided by said particular broadcast source using a) a data identifier and b) a table identifier.

13. A method for forming composite program guide information from program guide information received from a plurality of different broadcast sources, said program guide information from an individual broadcast source containing system timing data comprising a current time reference indication provided by said individual broadcast source, comprising the steps of:

forming channel map information including at least one identification number for use in identifying a broadcast channel and for associating said broadcast channel with a broadcast source;

incorporating said channel map information and current time reference indications produced by a plurality of broadcast sources into said composite program guide information;

forming said composite program guide information to associate a particular current time reference indication with a particular individual broadcast source; and

incorporating said composite program guide information into packetized data for output to a transmission channel.

14. A system for initiating scheduled program processing functions using an electronic program guide for use in a video decoder receiving packetized program information from different broadcast sources, said packetized program information from an individual broadcast source containing program content, a current time reference indication and program specific information data, comprising:

selection means for selecting a desired program produced by a broadcast source;

means for tuning to receive packetized program information containing said desired program;

a processor for initiating scheduled processing of said desired program in response to a user selection made via a displayed electronic program guide, said processor initiates said scheduled processing using a time clock derived from a current time reference indication produced by a particular broadcast source associated with said desired program; and

means for displaying a second time clock different to said derived time clock.

15. A system according to claim 14, wherein

said second time clock is a filtered time clock to prevent a user from discerning a time change discontinuity.

16. A system according to claim 14, wherein

said second time clock is updated during periods when said second time clock is not displayed to prevent a user from discerning a time change discontinuity.

17. A system according to claim 14, wherein

said second time clock is updated using current time reference indications from a single source.

18. A system according to claim 14, wherein

said second time clock is independent of said derived time clock and is received in a dedicated program guide channel.

19. A system according to claim 18, wherein said second time clock is embedded in the content of said dedicated program guide channel.

20. A system according to claim 18, wherein said second time clock is presented in said displayed electronic program guide.

21. A method for initiating scheduled program processing functions for use in a video decoder receiving packetized program information from different broadcast sources, said packetized program information from an individual broadcast source containing program content, system timing and program specific information data, comprising the steps of:

tuning to receive packetized program information containing a desired program produced by a broadcast source;

identifying and acquiring system timing data comprising a current time reference indication received from said broadcast source in said packetized program information;

deriving a time clock based on a current time reference indication produced by a particular broadcast source; and

initiating scheduled processing functions for programs from said particular broadcast source using said derived time clock.

22. A method according to claim 21 including the step of

disregarding a time clock derived from a current time reference indication produced by a source other than said particular broadcast source.

23. A system according to claim 21, wherein said initiating scheduled processing functions step comprises

initiating a function including at least one of, a) program recording, b) program playback and c) program tuning and display.

24. A method for initiating scheduled program processing functions using an electronic program guide for use in a video decoder receiving packetized program information from different broadcast sources, said packetized program information from an individual broadcast source containing program content, a current time reference indication and program specific information data, comprising the steps of:

selecting a desired program produced by a broadcast source;

tuning to receive packetized program information containing said desired program;

deriving a time clock from a current time reference indication received from a particular broadcast source associated with said desired program;

initiating scheduled processing of said desired program using said derived time clock in response to a user selection made via a displayed electronic program guide; and

means for displaying a second time clock different to said derived time clock.

Abstract

A system for initiating scheduled program processing functions such as program display, recording or playback, derives a time clock based on a current time reference indication produced by a particular broadcast source. The derived time clock is used in initiating scheduled processing functions for programs derived from the particular broadcast source and time clocks derived from sources other than the particular broadcast source are disregarded. The system displays a second time clock different to the derived time clock. In addition, the system forms a composite program guide from data from multiple broadcast sources to associate current time reference indications with their corresponding broadcast sources.

FIGURE 1.



1/5

FIGURE 2


START
200
SCHEDULE PROCESSING OF A DESIRED PROGRAM INCLUDING:
A) PROGRAM RECORDING,
B) PROGRAM PLAYBACK, OR
C) PROGRAM TUNING AND DISPLAY
203
TUNE TO RECEIVE PACKETIZED PROGRAM INFORMATION CONTAINING THE DESIRED PROGRAM PRODUCED BY A BROADCAST SOURCE
205
IDENTIFY AND ACQUIRE SYSTEM TIMING DATA COMPRISING A CURRENT TIME REFERENCE INDICATION RECEIVED FROM THE BROADCAST SOURCE IN THE PACKETIZED PROGRAM INFORMATION
210
DERIVE A TIME CLOCK BASED ON THE CURRENT TIME REFERENCE INDICATION PRODUCED BY THE BROADCAST SOURCE
215
USE THE DERIVED TIME CLOCK TO UPDATE A STORED SCHEDULING CLOCK
220
INITIATE SCHEDULED PROCESSING OF THE DESIRED PROGRAM USING THE SCHEDULING TIME CLOCK DERIVED FROM THE BROADCAST SOURCE PRODUCING THE PROGRAM, AND DISREGARD A TIME CLOCK DERIVED FROM A SOURCE OTHER THAN THE BROADCAST SOURCE OF THE DESIRED PROGRAM.
225
DISPLAY A FILTERED TIME CLOCK THAT IS DIFFERENT TO THE DERIVED TIME CLOCK
230
END
235

FIGURE 3



FIGURE 4


START
300
INITIATE SCHEDULING OF PROCESSING OF A DESIRED PROGRAM INCLUDING: A) PROGRAM RECORDING, B) PROGRAM PLAYBACK, OR C) PROGRAM TUNING AND DISPLAY
303
TUNE TO RECEIVE COMPOSITE PROGRAM GUIDE INFORMATION CONTAINING PROGRAM SPECIFIC INFORMATION ASSOCIATED WITH THE DESIRED PROGRAM PRODUCED BY A FIRST BROADCAST SOURCE
305
RETRIEVE FROM MEMORY A PROGRAM SPECIFIC INFORMATION PARAMETER COMPRISING A PROGRAM CONTENT RATING OF THE DESIRED PROGRAM RECEIVED FROM THE FIRST BROADCAST SOURCE
310
1) VALIDATE USER AUTHORIZATION TO ACCESS THE DESIRED PROGRAM BY COMPARING THE PROGRAM CONTENT RATING FROM THE FIRST BROADCAST SOURCE WITH A PREDETERMINED USER SPECIFIC RATING PROFILE COMPRISING A MAXIMUM RATING THRESHOLD THAT IS SUBJECT TO OVERRIDE.
2) SCHEDULE PROGRAM PROCESSING UPON SUCCESSFUL VALIDATION.
315
DETERMINE A PROGRAM CONTENT RATING OF THE DESIRED PROGRAM FROM A PROGRAM SPECIFIC INFORMATION PARAMETER RECEIVED FROM A SECOND BROADCAST SOURCE
320
MAP THE PROGRAM CONTENT RATING FROM THE SECOND SOURCE TO A CONTENT RATING SYSTEM OF THE FIRST SOURCE
325
SELECT A PROGRAM SPECIFIC INFORMATION PARAMETER (A PROGRAM CONTENT RATING IN THIS EXAMPLE) BASED ON THE BROADCAST SOURCE OF THE PARAMETER AND DISPLAY THE RATING IN A PROGRAM GUIDE, FOR EXAMPLE.
330
VALIDATE USER AUTHORIZATION TO ACCESS THE DESIRED PROGRAM BY COMPARING THE SELECTED PROGRAM CONTENT RATING WITH A PREDETERMINED USER SPECIFIC RATING PROFILE COMPRISING A MAXIMUM RATING THRESHOLD
335
INITIATE PROCESSING OF THE DESIRED PROGRAM UPON SUCCESSFUL VALIDATION OF USER AUTHORIZATION TO ACCESS THE DESIRED PROGRAM
337
END
340

FIGURE 5



Express Mail Label No. EL213822368US

RCA 89041

DECLARATION AND POWERS OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled A SYSTEM FOR PROCESSING PROGRAMS AND SYSTEM TIMING INFORMATION DERIVED FROM MULTIPLE BROADCAST SOURCES the specification of which was filed on _____ as Application Serial No. _____ and was amended on _____, or, if not identified here by filing date and serial number, is attached hereto.

I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 USC 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate by me or my representatives or assigns for this invention having a filing date before that of the application on which priority is claimed.

Application No. _____ in _____ on _____ priority claimed [ ] Yes [ ] No
Application No. _____ in _____ on _____ priority claimed [ ] Yes [ ] No
Application No. _____ in _____ on _____ priority claimed [ ] Yes [ ] No

I hereby claim the benefit under 35 USC 119(e) of any United States provisional application(s) as listed below.

Application No. 60/092,616 Filed July 13, 1998
Application No. _____ Filed _____

I hereby claim the benefit under 35 USC 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of 35 USC 112, I acknowledge the duty to disclose material information as defined in 37 CFR 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application

Serial No. _____ Filed _____ [ ] patented [ ] pending [ ] abandoned
Serial No. _____ Filed _____ [ ] patented [ ] pending [ ] abandoned

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 USC 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I hereby appoint, individually and collectively, the following as my/our attorney or agent with full power of substitution and revocation, to prosecute this application and to transact all business in the U.S. Patent and Trademark Office connected therewith:

Joseph S. Tripoli Registration No. 26,040 and
Eric P. Herrmann Registration No. 29,169 and
Ronald H. Kurdyla Registration No. 26,932 and
Alexander J. Burke Registration No. 40,425

PLEASE ADDRESS ALL COMMUNICATIONS TO: JOSEPH S. TRIPOLI
PATENT OPERATIONS - GE AND RCA
LICENSING MANAGEMENT OPERATION, INC.
P.O. Box 5312
PRINCETON, NEW JERSEY 08543-5312

Sole or Joint Inventor (1) Daniel Richard Schneidewend (Type or Print) — Daniel Richard Schneidewend (Signature in Full. No initials.)
Citizenship United States Date 10/30/98
Post Office Address Fishers, Hamilton County, Indiana
Residence 11221 Tall Trees Drive, Fishers, Indiana 46038

Sole or Joint Inventor (2) Aaron Hal Dinwiddie (Type or Print) — Aaron Hal Dinwiddie (Signature in Full. No initials.)
Citizenship United States Date 11/8/98
Post Office Address Fishers, Hamilton County, Indiana
Residence 12466 Trohpy Drive, Fishers, Indiana 46038

Sole or Joint Inventor (3) _____ (Type or Print) _____ (Signature in Full. No initials.)
Citizenship _____ Date _____
Post Office Address _____
Residence _____